#### INVESTIGATIVE REPORT

ON

#### SUBSURFACE PETROLEUM CONTAMINATION

 $\mathbf{AT}$ 

# CAPITOL MOBIL, 108 STATE STREET MONTPELIER, VERMONT

**VTDEC SITE # 92-1277** 

MAY 28, 1993

Prepared for:

Premium Petroleum Inc. 32 San Remo Drive South Burlington, VT 05403

Prepared by:

Griffin International, Inc. 2B Dorset Lane Williston, VT 05495

#### TABLE OF CONTENTS

#### SECTION

- I. INTRODUCTION
- II. SITE DESCRIPTION
- III. INVESTIGATIVE PROCEDURES
  - A. Monitoring Well Installation
  - B. Groundwater Sampling and Analysis
  - C. Determination of Groundwater Flow Direction and Gradient
  - D. Receptor Survey
- IV. RISK ASSESSMENT
- V. CONCLUSIONS
- VI. RECOMMENDATIONS

Appendix A: Site Maps Appendix B: Well Logs

Appendix C: Laboratory Results Appendix D: Liquid Level Data

#### I. INTRODUCTION

On August 5, 1992, a 1000 gallon underground storage tank (UST) was removed from Capitol Mobil on State Street in Montpelier. The tank contained heating oil. A tank pull inspection was conducted by Wagner, Heindel and Noyes, Inc. of Burlington Vermont, which indicated the presence of petroleum contamination in the surrounding soils. Groundwater was not present at that time. The amount and duration of the presumed leak is not known.

The Vermont Department of Environmental Conservation (VTDEC) requested additional investigation at the site to determine the degree and extent of contamination, identify potential receptors, and prepare conclusions and recommendations based on the results of the investigation. Griffin International Inc. (Griffin) has been retained by the owner, Premium Petroleum Inc., to provide these services. Griffin has prepared this report in compliance with the revised and approved Work Plan dated March 30, 1993.

#### II. SITE DESCRIPTION

The site is located in downtown Montpelier on the corner of State Street and Taylor Street, which is a dense commercial zone. There are several State office buildings adjacent to the site, as well as a Days Inn Hotel immediately east of the property and a Gulf gas station located across State Street to the north. A site map is included in Appendix A.

Most surfaces are level asphalt paving or concrete sidewalks which drain into several catch basins along the curbs. The Winooski River is approximately 300 feet south of the property and flows east to west.

Montpelier is served by both municipal water and sewer systems, which are located under Taylor Street on the west side of the property. Capitol Mobil connects to these utilities from the west side of the building.

Geologic maps indicate a recent alluvium sand and gravel overburden with dolomite bedrock. Exploratory drilling appeared to confirm this data.

#### III. INVESTIGATIVE PROCEDURES

In order to further define the extent and degree of subsurface petroleum contamination, Griffin installed two additional groundwater monitoring wells, MW4 and MW5, in the presumed down gradient direction from the former UST. The three existing wells (MW1, MW2, MW3) installed on February 3, 1992, are presumed to be upgradient of the former UST. Water samples collected from all five wells were analyzed to help define the contamination concentrations and migration trends at the site. The site was surveyed to



May 28, 1993

Mr. Richard Spiese Vermont Dept. of Environmental Conservation H.M.M.D. 103 South Main St. Waterbury, VT 05671-0404

RE: Capitol Mobil, VTDEC Site # 92-1277

Dear Mr. Spiese,

Griffin International has completed the initial investigation of subsurface petroleum contamination at Capitol Mobil in Montpelier, VT. Our enclosed report details the investigative procedures and also includes conclusions and recommendations. If you have any questions, please call anytime.

Sincerely

Peter Hack Engineer

cc: Mr. David Simendinger

provide locations and elevations of major site features, including the five monitoring wells. Water table elevations were also measured to determine groundwater flow data. All collected data is used to study the present contamination levels and predict its effects on the surrounding potential receptors.

#### A. Monitoring Well Installation

On April 13, 1993 two groundwater monitoring wells were installed by Green Mountain Boring of Barre, Vermont, under the direct supervision of a Griffin engineer. The wells were installed using a hollow stem auger drill rig. Undisturbed soil samples were collected with a split spoon sampler at five foot depth increments in each well. These samples were field screened for volatile organic compounds (VOCs) with an HNU PI101 portable photo-ionization device (PID). The soil samples were also used to determine subsurface soil characteristics. Drilling and PID screening data are included in Appendix B.

The wells are constructed of 2 inch diameter 0.01" slotted PVC well screen and casing. The annulus between the borehole wall and the well screen contains a silica gravel pack to filter fine sediments from entering the well. The top of the annulus is sealed with a bentonite plug to prevent surface waters from directly entering the borehole. Each well has a locking cap and a flush mounted protective steel cover.

The two wells were strategically located to provide information on the possible migration of contaminants. MW4 was installed in a location that was assumed to be downgradient of the known contamination. This well has been used to determine the vertical and horizontal extent of contamination in this area. MW5 was installed directly in the tank pit excavation. This well has provided data relating to the vertical and horizontal extent of contamination at the apparent source. All five wells have been monitored to determine the groundwater gradient and any paths that the contamination may take.

Q17 . ?

÷.

Soil samples collected from MW4 contained VOC concentrations of 0.4 ppm at a depth of 4'-6' when screened with a PID. At a depth of 14'-16' in this well VOC concentrations up to 130 ppm were detected. Strong petroleum odors were present and the wet soil samples contained visible sheens. The soil samples generally ranged from sand at the surface to silt, coarse sand and gravel at 14'-16' below grade. Bedrock was not encountered.

Soil samples collected from MW5 contained VOC concentrations of 15 ppm at a depth of 4'-6' below grade. PID readings of soils collected at 9'-11' in this borehole indicated VOC concentrations of 200 ppm. At 14'-16' the soils contained VOC concentrations of 100 ppm. This soil sample also had a strong petroleum odor and visible sheens. Soil collected from MW5 ranged from sands, gravel and fills near the surface to coarse sand and gravel at the base of the exploration. Bedrock was encountered at 16' below grade. Soil boring logs are included in Appendix B.

#### B. Groundwater Sampling and Analysis

On April 20, 1993, Griffin collected groundwater samples from all five wells on site. The sample collected from MW5 contained approximately 1/8" of free product and therefore was not analyzed at the laboratory. All other water samples (MW1 thru MW4) were collected per Griffin's sampling protocol and analyzed to EPA Methods 8020 and 418.1. The 8020 analysis detects the presence of BTEX compounds (benzene, toluene, ethylbenzene and xylenes) and MTBE (methyl tertiary butyl ether). The 418.1 analysis indicates TPH, or Total Petroleum Hydrocarbons.

The EPA Method 8020 laboratory analysis of the water sample collected from MW1 did not detect any BTEX or MTBE compounds. However, a TPH concentration of 2.0 parts per million (ppm) was detected in this sample by EPA Method 418.1 analysis.

The EPA Method 8020 analysis of the water sample collected from MW2 indicated concentrations of ethylbenzene, toluene, and xylenes of 2070 parts per billion (ppb), 3370 ppb, and 6630 ppb, respectively. A trace of benzene was also detected in MW2. EPA Method 418.1 analysis of the sample from MW2 indicated a TPH concentration of 3.3 ppm.

The EPA 8020 analysis of the water sample collected from MW3 also detected concentrations of BTEX compounds. The lab results indicated concentrations of 1150 ppb of ethylbenzene, 3360 ppb of toluene, 4750 ppb of xylenes and 850 ppb of benzene. EPA Method 418.1 analysis of the sample from MW3 indicated a TPH concentration of 4.1 ppm.

The water sample from MW4 also contained elevated concentrations of BTEX and MTBE compounds. EPA 8020 analysis of this sample detected 95.2 ppb of ethylbenzene, 52.7 ppb of toluene, 114 ppb of xylenes, 166 ppb of benzene and 739 ppb of MTBE. EPA Method 418.1 analysis of the sample from MW4 indicated a TPH concentration of 55 ppm.

Most of the MTBE and BTEX concentrations detected in these water samples are above the Vermont Drinking Water Standards. The VDWS health advisory levels for BTEX and MTBE are 5 ppb for benzene, 680 ppb for ethylbenzene, 2420 ppb for toluene, 400 ppb for xylenes and 40 ppb for MTBE.

The presence of MTBE in monitoring well #4 indicates that a portion of subsurface petroleum contamination at the site consists of gasoline.

Duplicate, trip blank and equipment blank samples indicate that quality assurance and quality control were maintained during sampling and analysis. The QA/QC results are included in Appendix C with the groundwater results.

thin dill dies in the present in the

#### C. Groundwater Flow Direction and Gradient

The water table elevations are shown on the Groundwater Contour Map in Appendix D. The elevations are based on an arbitrary datum of 100 feet taken at the top of the casing of Monitoring Well #2. The map indicates that the groundwater appears to be flowing to the south west toward the river as predicted. The average water table gradient in the immediate vicinity is calculated to be 0.3 %. Liquid level data collected on April 20, 1993 is included in Appendix D.

#### D. Receptor Survey

Griffin conducted a visual survey of the site to locate and identify potential receptors of subsurface petroleum contaminants. Potential receptors identified include the Capitol Mobil building, the storm drain system, adjacent buildings, and the Winooski River. This section of the city of Montpelier is served by municipal water and sewer lines located under Taylor Street. There are no water supply wells in the area.

The Mobil building is built on a concrete slab on grade and is not considered a likely receptor of petroleum vapors originating from subsurface contamination. Other adjacent buildings are believed to have below grade basements that would be considered potential receptors of vapors. To date, there have been no reports of petroleum vapors in adjacent buildings.

The site surface consists of asphalt paving and concrete sidewalks, which drain into a series of catch basins. The outfall of the storm drain was not apparent at the time of this investigation.

The Winooski River is located about 300 feet south of the property. It appears that the groundwater may flow in this direction, however, due to this considerable distance, it is not likely that significant contamination concentrations will reach the river.

#### V. CONCLUSIONS

Based on the data collected during this investigation, Griffin presents the following conclusions.

1) There have been releases of petroleum to the subsurface in the vicinity of Capitol Mobil resulting in soil and groundwater contamination. The flood of 1992 was a major cause of releases in the area from basement heating oil tanks along State Street. It is possible that these releases resulted in soil and groundwater contamination in the area.

- 2) The 1000 gallon UST, a suspected source of subsurface petroleum contamination, was removed in August 1992. The contents of this tank were not tested and it is not clear if this tank was the source of the MTBE found in MW4.
- 3) Residual dissolved phase contamination is present in the subsurface at this site.

  Analysis of the groundwater samples indicate that many wells show concentrations of benzene, ethylbenzene, toluene, xylenes and MTBE to be above the Vermont Drinking Water Standards. However, the analysis of the groundwater sample from MW1, in the southeast corner of the site closest to the Days Inn, did not indicate the presence of petroleum contamination.
- 4) Groundwater in the vicinity of Capitol Mobil flows southwest at a hydraulic gradient of 0.3 %.
- 5) The only affected receptors detected during this investigation are the soils and groundwater at the site. Other possible receptors include the basement of the state building (hydraulically downgradient and south-west across Taylor Street), the storm water system and the Winooski River.

#### VI. RECOMMENDATIONS


Due to the contamination concentrations that were detected in water samples collected on site, Griffin recommends resampling of the five on-site monitoring wells and screening of the ambient air in nearby basements. Sampling and screening should take place once a quarter for the first year to determine the site parameters and to develop a baseline for monitoring and tracking the contamination. After this data is analyzed, a better determination of the need for future remediation, monitoring or site closure can be made.


# APPENDIX A


Site Location Map Site Map Groundwater Contour Map

## SITE LOCATION MAP FOR CAPITOL MOBIL

STATE STREET, MONTPELIER, VT







# APPENDIX B

Well Logs

•	ROJECT CAPITAL MOBIL
IAMETER 6"  CREEN DIA. 2" LENGTH 10' SLOT SIZE .010"  ASING DIA. 2" LENGTH 5' TYPE PVC  RILLING CO. GRN MT BORING DRILLING METHOD HOLLOW STEM AUG	OCATION MONTPELIER, YT
CREEN DIA. 2" LENGTH 10' SLOT SIZE .010"  ASING DIA. 2" LENGTH 5' TYPE PVC  RILLING CO. GRN MT BORING DRILLING METHOD HOLLOW STEM AUG	ATE DRILLED 4/13/93 TOTAL DEPTH OF HOLE 15
ASING DIA. 2" LENGTH 5" TYPE PYC PYC RILLING CO. GRN MT BORING DRILLING METHOD HOLLOW STEM AUG	IAMETER6"
RILLING CO. GRN MT BORING DRILLING METHOD HOLLOW STEM AUG	
•	ASING DIA. 2" LENGTH5' TYPEPVC
ORILLER MIKE, BOB LOG BY P HACK	RILLING CO. GRN MT BORING DRILLING METHOD HOLLOW STEM AUGE
	RILLER MIKE, BOB LOG BY PHACK

WELL NUMBER 11W-4				
ŤN	M∀-5	) j	• M₩-3	• "
MW-	-4	•MW-	2	MW-1
Ū	CAP	ITAL M	OBIL	

DEPTH IN FEET	WELL CONSTRUCTION	NOTES	BLOWS PER 6" of SPOON and PID readings	DESCRIPTION / SOIL CLASSIFICATION (COLOR, TEXTURE, STRUCTURES)
- 0 - - 1 - - 2 - - 3 -		ROAD BOX WELL CAP NATIVE FILL BENTONITE		LIGHT BROWN,DRY,SAND
- 4 - - 5 - - 6 -		— RISER — GRAVEL PACK	4'-6':10,6,3 PID=0.4PPM	BROWN, MOIST, FINE SAND AND SILT SOME STAINING
- 8 - - 9 - -10 - -11 - -12 -		well screen	9'-11':2,2,2,5	<u>₩ATER TABLE</u> GOLD-BROWN,MOIST, SILT,  STAINS, ODORS
-13 - -14 - -15 -			14'-16':7,5,10,5 PID=130PPM	BLACK, WET, COARSE SAND TO GRAVEL STRONG ODORS AND SHEENS
17 18	-		1	BASE OF EXPLORATION @ 16'
-20 - -21 - -22 -				
23 - 24 - 25 - 26 -	  - 			
	<u> </u>	<u></u>	<del>, L </del>	<del></del>

Griffin International

REF:PAINT50

PIDE?

ROJECT CAPITAL MUBIL
OCATION MONTPELIER, YT
ATE DRILLED 4/13/93 TOTAL DEPTH OF HOLE .15"
4AMETER6"
CREEN DIA. 2" LENGTH 10' SLOT SIZE .010"
ASING DIA. 2" LENGTH 5" TYPE PYC
PRILLING CO. GRN MT BORING DRILLING METHOD HOLLOW STEM AUGER
RILLER MIKE, BOB LOG BY PHACK

_	WELL N	UMBER	MW-5	
	În c	∰' () Mw'-5	• M₩-3	
	M∀-4 • —	• MW	′-2 	M₩- <b>[</b>
		CAPITAL 1	MOBIL	

		····	<u> </u>	
DEPTH IN FEET	WELL CONSTRUCTION	NOTES	BLOWS PER 6" of SPOON and PID readings	DESCRIPTION / SOIL CLASSIFICATION (COLOR, TEXTURE, STRUCTURES)
- 0 -		— ROAD BOX WELL CAP NATIVE FILL		ASPHALT
- 2 <del>-</del>		BENTONITE		. •
- 4 - - 5 -		RISER	4'-6':11,8,7,9 PID=15PPM	DARK BROWN, DAMP, SAND AND GRAVEL SOME FILL DEBRIS,
6 -		— GRAVEL PACK		
- 7 - - 8 -				GRAY/GREEN,DAMP,SILT
- 9 - -10-			9'-11':3,1,1,2 PID=200PPM	SOME BLACK STAINS, SOME ODORS WATER TABLE
-11-		WELL SCREEN		<del></del>
-12- -13-				
14 15			14'-16':4,5,13,17 PID=100PPM	BLACK, WET, COARSE SAND AND GRAVEL, STRONG ODOR, SHEENS BEDROCK @ 16*
-16 - -17 -	7.7.7. <del>1.</del> 17.7.7			BOTTOM OF EXPLORATION @ 16'
-18 -				
20 -				
- 21 - - 22 -				
- 23 -				
- 24 - - 25 -				
_26 <u>_</u>				Criffin International

Griffin International REF:PAINT50

# APPENDIX C

**Laboratory Results** 



32 James Brown Drive Williston, Vermont 05495 (802) 879-4333 FAX 879-7103

#### REPORT OF LABORATORY ANALYSIS

CLIENT: Griffin International PROJECT NAME: Capital Mobil REPORT DATE: May 5, 1993

REPORT DATE: May 5, 1993 DATE SAMPLED: April 20, 1993 PROJECT CODE: GICP1394

REF.#: 44,756 - 44,762

Enclosed please find the results of the analyses performed for the samples referenced on the attached chain of custody. Chain of custody indicated samples were preserved with HCl.

All samples were prepared and analyzed by requirements outlined in the referenced method and within the specified holding times. All instrumentation was calibrated with the appropriate frequency and verified by the requirements outlined in the referenced method. Blank contamination was not observed at levels affecting the analytical results.

Analytical method precision and accuracy was monitored by laboratory control standards which included matrix spike, duplicate and quality control analyses. These standards were determined to be within established laboratory method acceptance limits.

Individual sample performance was monitored by the addition of surrogate analytes to each sample. All surrogate recovery data was determined to be within laboratory QA/QC guidelines unless otherwise noted.

Reviewed by

Harry B. Locker, Ph.D. Laboratory Director

enclosures



32 James Brown Drive Williston, Vermont 05495 (802) 879-4333 FAX 879-7103

#### LABORATORY REPORT

RECEIVED MAY 1 0 1993

#### **EPA METHOD 602 -- PURGEABLE AROMATICS**

CLIENT: Griffin International PROJECT NAME: Capital Mobil REPORT DATE: May 5, 1993 DATE SAMPLED: April 20, 1993 DATE RECEIVED: April 20, 1993

ANALYSIS DATE: April 29, 1993

PROJECT CODE: GICP1394

REF.#: 44,756 STATION: MW-1

TIME SAMPLED: 12:09 SAMPLER: J. Bernhard

<u>Parameter</u>	Detection Limit (ug/L)	Concentration (ug/L)
<b>D</b>	4	27721
Benzene	i	$ND^1$
Chlorobenzene	1	ND
1,2-Dichlorobenzene	1	ND
1,3-Dichlorobenzene	. 1	ND
1,4-Dichlorobenzene	1	ND
Ethylbenzene	1	ND
Toluene	1	ND
Xylenes	1	ND
MTBE	5	ND

Bromobenzene Surrogate Recovery: 100%

NUMBER OF UNIDENTIFIED PEAKS FOUND: 1

#### NOTES:

1 None detected



32 James Brown Drive Williston, Vermont 05495 (802) 879-4333 FAX 879-7103

#### LABORATORY REPORT

RECEIVED MAY 1 0 1993

#### EPA METHOD 602 -- PURGEABLE AROMATICS

CLIENT: Griffin International PROJECT NAME: Capital Mobil

REPORT DATE: May 5, 1993

DATE SAMPLED: April 20, 1993 DATE RECEIVED: April 20, 1993 ANALYSIS DATE: April 29, 1993 PROJECT CODE: GICP1394

REF.#: 44,757 STATION: MW-2

TIME SAMPLED: 12:51

SAMPLER: J. Bernhard

<u>Parameter</u>	Detection Limit (ug/L)1	Concentration (ug/L)
Benzene	1000	$TBQ^{2}$
Chlorobenzene	1000	$ND^3$
1,2-Dichlorobenzene	1000	ND
1,3-Dichlorobenzene	1000	ND
1,4-Dichlorobenzene	1000	ND .
Ethylbenzene	1000	2,070.
Toluene	1000	3,370.
Xylenes	1000	6,630.
MTBE	5000	3,370. 6,630. (enc) by ND
Brome	obenzene Surrogate Recovery	

#### NUMBER OF UNIDENTIFIED PEAKS FOUND: 0

- 1 Detection limit raised due to high levels of contaminants. Sample run at 0.1% dilution.
- 2 Trace below quantitation limit
- 3 None detected



32 James Brown Drive Williston, Vermont 05495 (802) 879-4333 FAX 879-7103

#### LABORATORY REPORT

RECEIVED NAV 1 0 1893

#### EPA METHOD 602 -- PURGEABLE AROMATICS

CLIENT: Griffin International

PROJECT NAME: Capital Mobil REPORT DATE: May 5, 1993

DATE SAMPLED: April 20, 1993 DATE RECEIVED: April 20, 1993 ANALYSIS DATE: April 29, 1993 PROJECT CODE: GICP1394

REF.#: 44,758 STATION: MW-3

TIME SAMPLED: 13:23 SAMPLER: J. Bernhard

<u>Parameter</u>	Detection Limit (ug/L)1	Concentration (ug/L)
Dangana	500	850.
Benzene		
Chlorobenzene	500	$ND^2$
1,2-Dichlorobenzene	500	ND
1,3-Dichlorobenzene	500	ND
1,4-Dichlorobenzene	500	ND
Ethylbenzene	500	1,150.
Toluene	500	3,360.
Xylenes	500	4,750.
MTBE	2500	ND

Bromobenzene Surrogate Recovery: 102%

#### NUMBER OF UNIDENTIFIED PEAKS FOUND: 3

- 1 Detection limit raised due to high levels of contaminants. Sample run at 0.2% dilution.
- 2 None detected



32 James Brown Drive Williston, Vermont 05495 (802) 879-4333 FAX 879-7103

RECEIVED HAY 1 0 1993

#### LABORATORY REPORT

#### **EPA METHOD 602 -- PURGEABLE AROMATICS**

CLIENT: Griffin International

PROJECT NAME: Capital Mobil REPORT DATE: May 5, 1993

DATE SAMPLED: April 20, 1993 DATE RECEIVED: April 20, 1993

ANALYSIS DATE: May 4, 1993

PROJECT CODE: GICP1394

REF.#: 44,759

STATION: MW-4

TIME SAMPLED: 13:52 SAMPLER: J. Bernhard

<u>Parameter</u>	Detection Limit (ug/L)1	Concentration (ug/L)
Benzene	20	166.
Chlorobenzene	20	$ND^2$
1,2-Dichlorobenzene	20	ND
1,3-Dichlorobenzene	. 20	ND
1,4-Dichlorobenzene	20	ND
Ethylbenzene	20	95.2
Toluene	20	52.7
Xylenes	20	114.
MTBE	100	739.

Bromobenzene Surrogate Recovery: 87%

#### NUMBER OF UNIDENTIFIED PEAKS FOUND: 15

- 1 Detection limit raised due to high levels of contaminants. Sample run at 5% dilution.
- 2 None detected



32 James Brown Drive Williston, Vermont 05495 (802) 879-4333 FAX 879-7103

#### LABORATORY REPORT

RECEIVED HAY I 9 1992

#### **EPA METHOD 602 -- PURGEABLE AROMATICS**

CLIENT: Griffin International PROJECT NAME: Capital Mobil REPORT DATE: May 5, 1993

DATE SAMPLED: April 20, 1993
DATE RECEIVED: April 20, 1993

ANALYSIS DATE: April 29, 1993

PROJECT CODE: GICP1394

REF.#: 44,760

STATION: Duplicate (MW-2)

TIME SAMPLED: 12:51 SAMPLER: J. Bernhard

<u>Parameter</u>	Detection Limit (ug/L)1	Concentration (ug/L)
n	1000	mod
Benzene	1000	(TBQ2/
Chlorobenzene	1000	ND <sup>3</sup>
1,2-Dichlorobenzene	1000	ND
1,3-Dichlorobenzene	1000	ND
1,4-Dichlorobenzene	1000	ND
Ethylbenzene	1000	2,210.
Toluene	1000	3,520.
Xylenes	1000	7,090.
MTBE	5000	ND

Bromobenzene Surrogate Recovery: 104%

#### NUMBER OF UNIDENTIFIED PEAKS FOUND: 0

- 1 Detection limit raised due to high levels of contaminants. Sample run at 0.1% dilution.
- 2 Trace below quantitation limit
- 3 None detected



32 James Brown Drive Williston, Vermont 05495 (802) 879-4333 FAX 879-7103

#### LABORATORY REPORT

RECEIVED MAY 1 0 1993

#### **EPA METHOD 602 -- PURGEABLE AROMATICS**

CLIENT: Griffin International PROJECT NAME: Capital Mobil REPORT DATE: May 5, 1993 DATE SAMPLED: April 20, 1993 DATE RECEIVED: April 20, 1993 ANALYSIS DATE: April 29, 1993 PROJECT CODE: GICP1394

REF.#: 44,761

STATION: Trip Blank TIME SAMPLED: 7:50 SAMPLER: J. Bernhard

<u>Parameter</u>	Detection Limit (ug/L)	Concentration (ug/L)
Benzene	1	$ND^{1}$
Chlorobenzene	1	ND
1,2-Dichlorobenzene	1	ND
1,3-Dichlorobenzene	. 1	ND
1,4-Dichlorobenzene	1	ND .
Ethylbenzene	1	ND
Toluene	1	ND
Xylenes	1	ND
MTBE	5	ND

Bromobenzene Surrogate Recovery: 99%

NUMBER OF UNIDENTIFIED PEAKS FOUND: 0

NOTES:

1 None detected



32 James Brown Drive Williston, Vermont 05495 (802) 879-4333 FAX 879-7103

#### LABORATORY REPORT

RECEIVED MAY 1 0 1993

#### EPA METHOD 602 -- PURGEABLE AROMATICS

CLIENT: Griffin International PROJECT NAME: Capital Mobil REPORT DATE: May 5, 1993 DATE SAMPLED: April 20, 1993 DATE RECEIVED: April 20, 1993 ANALYSIS DATE: April 29, 1993 PROJECT CODE: GICP1394

REF.#: 44,762

STATION: Eq. Blank TIME SAMPLED: 14:21 SAMPLER: J. Bernhard

<u>Parameter</u>	Detection Limit (ug/L)	Concentration (ug/L)
Benzene	1	$ND^1$
Chlorobenzene	1	ND
1,2-Dichlorobenzene	1	ND
1,3-Dichlorobenzene	. 1	ND
1,4-Dichlorobenzene	1	ND
Ethylbenzene	1	ND
Toluene	1	TBQ <sup>2</sup>
Xylenes	1	ND
MTBE	5	ND

Bromobenzene Surrogate Recovery: 99%

#### NUMBER OF UNIDENTIFIED PEAKS FOUND: 1

- 1 None detected
- 2 Trace below quantitation limits



32 James Brown Drive Williston, Vermont 05495 (802) 879-4333 FAX 879-7103

## EPA METHOD 602 LABORATORY REPORT RECEIVED MAY 1 0 1993

#### MATRIX SPIKE AND DUPLICATE LABORATORY CONTROL DATA

CLIENT: Griffin International PROJECT NAME: Capital Mobil REPORT DATE: May 5, 1993 DATE SAMPLED: April 20, 1993 DATE RECEIVED: April 20, 1993 ANALYSIS DATE: April 29, 1993 PROJECT CODE: GICP1394

REF.#: 44,756 STATION: MW-1

TIME SAMPLED: 12:09 SAMPLER: J. Bernhard

<u>Parameter</u>	Sample(ug/L)	Spike(ug/L)	Dup1(ug/L)	Dup2(ug/L)	Avg % Rec
Benzene	0	10	10.3	11.3	108%
Toluene	0	10	11.0	11.7	113%
Ethylbenzene	0	10	11.4	12.0	` 117%
Xylenes	0	30	32.3	34.1	111%

006630

## CHAIN-OF-CUSTODY RECORD

32 James Brown Drive Williston, Vermont 05495 (802) 879-4333

MAY	Project Nam Site Locatio	n: Morpelies, V	Mobel	Re	porting	Addro	ess: Griffing B. Ders Willis	7 Kn,	Lane		Billing Address: 50			
NED		ect Number: /93433/	4 GICP	/39 (Co	mpany ntaci	v: Gry: Name/P	41171 Hone #: 1-50	o-2	53-335	3	Sampler Name: July Phone #: Same	n 1)&50 h	450	
RECEIVED	Lab#	Sample Locat	lon	Matrix	G R A B	C O M P	Date/Time 4-20-93	Sampl No.	Containers Type/Size	: 466 : <b>16</b> 1	ield Results/Remarks	Analysis Required	Sample Preservation	Rush
/1	414756	mω-1	1	HaD			12:09	2	40m1			602	HCI	
	44757	mω-2	6.1				12:51	1			· · · · · · · · · · · · · · · · · · ·	<del> </del>	1 1/2	
·/[	U4135	mω-3	0.2				13:23	1/				$\bot V$	<del>           </del>	
$\emptyset$	44754	mω-4		_\\			13:52	*	V				<del>                                     </del>	
	47760		(mw-2)01				12:51							
	44701	Trip Blank	. 57				7:50					_		
$\sqrt{}$	44762	Egupnient	Blank				14:21						<del> </del>	
	···												-	
							<u></u>	<del> </del>				_	-	
							• •							
	Relinguished b	y: Signature		Re	ceived t	y: Signa	ture C/M	hZ.	ty		Date/Fine 4/2/9	<u> </u>	13' 15	Ст.
	Relinguished b	y: Signature		1		y: Signa	- // /	1			Date/l'ime			
	<u></u>				<u></u>		Requested A	nalys	ies					

xal P	12	TSS	17	Coliform (Specify)	22	EPA 625 B/N or A	27	EPA 8010/8020
			II I		11		th !	
stal Diss. P	13	TDS	18	COD	23	EPA 418.1	28	EPA 8080 Pest/PCB
OD.	14	Turbidity	19	BTEX	24	EPA 608 Pest/PCB		
_ <del></del>	15	Conductivity	F20 >	EPA 601/602	25	EPA 8240		
		DD <sub>1</sub> 14 calinity 15	DD 14 Turbidity calinity 15 Conductivity	DD, 14 Turbidity 19 calinity 15 Conductivity 20	DD, 14 Turbidity 19 BTEX  (alinity 15 Conductivity 20 EPA 601/602	DD, 14 Turbidity 19 BTEX 24  (alinity 15 Conductivity 20 EPA 601/602 25	DD 14 Turbidity 19 BTEX 24 EPA 608 Pest/PCB	D <sub>1</sub> 14 Turbidity 19 BTEX 24 EPA 608 Pest/PCB

14

# CHAIN-OF-CUSTODY RECORD

Project	Name: (	Reporti	ng Address: 67/	la de la companya de	Billing Address:		
Site Loc	ation: Mospeline VT		26.7	Kin Sign			
	Project Number	Compar Contact	iy: <i>CrUF ()</i> Name/Phone #: 1/-5	ir io '940:03	Sampler Names 73 Phone #		
Lab#	Sample Location	Matrix "G.	C Date/Time	Sample Containers	Field Results/Remarks	Analysis Samp	
14 28484	~ indites sease	istical His	12.09			1603 11 - H	7 413
	init gradity		1251				V WAR
	MU 3	83.44 P. 12	# W13:93				61 10 K.
TO THE REAL PROPERTY.	min-484		33 13 53	1 V 2 12 2 2 2 1 1 1 1 1 2 2 3 3 3 3 3 3 3			(# <b>37</b> 74)
1 9.7 2 2	207 asher Levelon		1010151	1.4.0.9 986 9 VO AC 5 79 0			
	the state of the s		37.50				
统为基础	Ega., 18	links	<b>16:41</b>				
in Miller		AND VIOLENCE OF A					
							11 11 23
				THE TANK TO			
				MODEL SHEETERS	4.100 2.100 2.100		
Kelinguishe	d by: Signature	Received	by Signature 5	16thy	Dais/Time		
Relinguishe	d by: Signature	Received	y Signature / Press	7/200	para epiernimo de est		
			Requested /	nalyses	Maria Ma		
1 pI	CONTRACTOR OF CIKN	AN ASSESSION DUE	otal Solids	16 Metals (Specify)	21% EPA 624	7.16 26 PEARLE	
	loride Total	* pages of these growing to the employing maters and the contract of the con-	1 1 1 1 1 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1	17 Coliform (Specif	a cracial with the profession of the second second of the second	TO STATE OF THE PARTY OF THE PA	2000
			and the season of the season o	18 COD			VPCB COPE
			····	19 BTEX 20 EPA 601/602	24 EPA 608 Pest/I		
	I.P (Specify: volstiles, semi-volstiles, metals,		Section 1				
<del></del>	her (Specify):						

32 James Brown Drive Williston, Vermont 05495 (802) 879-4333 FAX 879-7103

#### RECEIVED MAY 1 2 1983

#### REPORT OF LABORATORY ANALYSIS

CLIENT: Griffin International PROJECT NAME: Capital Mobil

DATE REPORTED: May 11, 1993 DATE SAMPLED: April 20, 1993 PROJECT CODE: GICP1395

REF. #: 44,763 - 44,769

Enclosed please find the results of the analyses performed for the samples referenced on the attached chain of custody record.

Chain of custody indicated samples were preserved with HCl.

All samples were prepared and analyzed by requirements outlined in the referenced methods and within the specified holding times.

All instrumentation was calibrated with the appropriate frequency and verified by the requirements outlined in the referenced methods.

Blank contamination was not observed at levels affecting the analytical results.

Analytical method precision and accuracy was monitored by laboratory control standards which included matrix spike, duplicate and quality control analyses. These standards were determined to be within established laboratory method acceptance limits.

Reviewed by,

Harry B. Locker, Ph.D. Laboratory Director

enclosures



32 James Brown Drive Williston, Vermont 05495 (802) 879-4333 FAX 879-7103

RECEIVED MAY 1 2 1000

#### LABORATORY REPORT

#### TOTAL HYDROCARBONS - EPA METHOD 418.1 (WATER)

CLIENT: Griffin International REPORT DATE: May 11, 1993 PROJECT NAME: Capital Mobil PROJECT CODE: GICP1395 DATE SAMPLED: April 20, 1993 DATE RECEIVED: April 20, 1993 DATE ANALYZED: May 10, 1993

SAMPLER: John Bernhard

Reference #	Sample ID	$\underline{\text{Conc.}}(\underline{\text{mg/L}})^1$
44,763	MW 1; 12:09	2.0
44,764	MW 2; 12:51	3.3
44,765	. MW 3; 13:23	4.1
44,766	MW 4; 13:52	55.
44,767	Duplicate (MW 2); 12:51	. 3.2
44,768	Trip Blank; 7:50	$ND^2$
44,769	Equipment Blank; 14:21	ND

#### Notes:

- 1 Method detection limit is 0.8 ppm
- 2 None detected



32 James Brown Drive Williston, Vermont 05495 (802) 879-4333 FAX 879-7103

RECEIVED MAY 1 2 1533

#### EPA METHOD 418 (WATER) LABORATORY REPORT

#### MATRIX SPIKE AND DUPLICATE LABORATORY CONTROL DATA

CLIENT: Griffin International PROJECT NAME: Capital Mobil REPORT DATE: May 11, 1993 DATE SAMPLED: April 20, 1993 DATE RECEIVED: April 20, 1993

ANALYSIS DATE: May 10, 1993

PROJECT CODE: GICP1395

REF.#: 44,763 STATION: MW-1

TIME SAMPLED: 12:09 SAMPLER: John Bernhard

<u>Parameter</u>	Sample(mg/L)	Spike(mg/L)	Dup 1(mg/L)	Dup 2(mg/L)	Avg % Recovery
Total Petroleum Hydrocarbons	2.0	10	10.2	11.9	· 91.
rryurocaroons	2.0	10	10.2	11.7	71.

	<b>ΞENDYNE</b> , ινα
محبسين :	32 James Brown Drive Williston, Vermont 05495

Other (Specify):

30

#### CHAIN-OF-CUSTODY RECORD

006632

(802	) 879-4333											<del></del> 1
Project Nam Site Locatio	n: Nontpelier, VT		Reportin	g Addr	ess: Corld	55 A	Lane		Billing Address: 52,7			
	ect Number:		Company	y: 6,5	///// Phone #: 1-50	·		53	Sampler Name: John Phone #: 50,000	Beenle	156	
Lab#	Sample Location	Matri	G R A B	C O M P	Date/Time		e Containers Type/Size	I	field Results/Remarks	Analysis Required	Sample Preservation	Rush
414163	MW·1	Hal	$\partial$		12:04	Q	11.165			415.1	11.1	
44764	mw-2				19:51	1,				1//	1.,_	
44765	mw-3	Ŋ,			/3/93	$\sqrt{}$						
11/11/16	mw-4	-γ			13.52						, , ,	
114769	Duplicate (MW.2)			<u> </u>	13:51		<u></u>			<u></u>		ļ
44168	Top Blank				7,50	<u> </u>						<u> </u>
44049	Equipment Rkink				14.21							
	/ * -			<u> </u>		<u> </u>	ļ			<u> </u>		<del> </del>
							ļ				<u> </u>	<del> </del>
· · · · · · · · · · · · · · · · · · ·											<del> </del>	<del> </del>
		į		<u> </u>	<u></u>		ļ				<del> </del>	<del> </del>
				<u> </u>	<u> </u>		<u> </u>					<u> </u>
Relinguished b	y: Signature /ohn K	/	Received	by: Signa	iture /m	160	(ty		Date/Time 4//20/4	3 6	<u>د ک</u> ک	nn
Relinguished by	y: Signature		Received	by: Signa	iture	7	/		Date/Time			

Rea	wested	Analyses
400	40000	

1	ρΗ	6	TKN	11	Total Solids	16	Metals (Specify)	21	EPA 624	26	EPA 8270 B/N or Acid
2	Chloride	7	Total P	12	TSS	17	Coliform (Specify)	22_	EPA 625 B/N or A	27	EPA 8010/8020
3	Ammonia N	8	Total Diss. P	13	TDS	18	COD	23	EPA 418.1	28	EPA 8080 Pest/PCB
4	Nitrite N	9	BOD	14	Turbidity	19	BTEX	24	EPA 608 Pest/PCB		<u></u>
5	Nitrate N	10	Alkalinity	15	Conductivity	20	EPA 601/602	25	EPA 8240		
29	TCLP (Specify: volatiles, sem	ú-volatile	s, metals, pesticides, herbicides)								



# CHAIN-OF-CUSTODY RECORD



3202/02/03	4.5.8/03 <b>4</b> 339.		ontact Name/I		Sample Containe	rs - 50 × 10 9	593475	Analysis	Cample 2
Lab#	Sample Location	n Matrix	A M	- Date/Time 9-20-93	No. Type/Size	=10.000.000.000	Results Remarks	Required P	
	MUST SERVICE	WARRY HIS U.		. 19:01/ 4.	2 11.ke	64223	7	E WELL	
	MUTAL IN	TO BEST OF CONTRACT	73.00	13/19/5/					
A PART I	MIDHRADE	13 888 A T		3273793	A= 3/\				
1400	arnitha 950 ses		144 452	(6)/3/57)	ie kine		144 525 11		
	Parkate (	MUTERI)	Sign Maria	1.13:51	351 355				
TO THE	Translant			3. n. so					
	E GLIVATION !	Renk San		24/42/					
	/4/3##W	AND THE PERSON NAMED IN		50 <b>2</b> 0203555	200		2500.03174		
	AND REAL PROPERTY.	MARKET WAS							
	e : water birkskein.	A CANADA MARA							
	Zint is seat the				ALL BANKS				
Relinguished by	Signature ///		Received by: Sign	nature ///	Kerti	"": " <sub>3</sub>	ate/Time 4//		333
Danie standard	TO TORRES	Service of the servic	resolute di trons analytich d	Comment of the State of State of	/18.300 / 16.00	ene vinderske skr	wo and hereby	74.4346.096.596	
Relinguished by	Signature	3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3	Received by: Sign	ature		i de la composición	ale/∏ime		
				Requested	Analyses 🖈	Starfe de	de diament	的議员推进的	
CALL CALLS		TKN	Total Sol	lide	16 Metals (Spe	city) , jak	1 EPA 624	84 120 DEX	870 BAN - A30
2 Chlorid	le		12 TSS	(3.3) 2条に「少年中間(2.4) 一年公司 日子	17% Coliform (S		district to consider a reference	公司等 [ ] [ ] [ ] [ ] [ ] [ ]	4 8010/8020 14 14 14 14 14 14 14 14 14 14 14 14 14
3 Ammo	nia N 1 2 2 2 2 2 2 3 8	Total Diss. P	13. TDS		18 COD	reversites and the	4 EPA 608 Pest/P	CB 129 CB	
4 Nitrite	N 4 2 2 2 3 2 3 2 3 2 3 2 3 2 3 2 3 2 3 2	BOD, C. J. A. S. E.		ivity (4.50 Less )	Table Mainten Bert	STATES AND ASSESSED OF THE PARTY OF THE PART	Jan State St		

# APPENDIX D

Liquid Level Data

# **LIQUID LEVEL MONITORING DATA**

PROJECT #: 193 4334
PROJECT NAME: Capital Mebil
LOCATION: Montpelier, VT

DATE: 4/20/93 SAMPLER: 7B. INSTRUMENTATION USED:

_		7	_		_	<u> </u>	<del>.                                    </del>	<del></del>	_	$\neg$	_	ī		ī	 	1	·
	TIME											•					
CORRECTED	WATER TABLE	ELEVATION	84.47	69.42	84.48	\$4.34	84.45										·
CORRECTED	DEPTH TO	WATER			-				•								
	HYDRO	EQUINILENT															
SPECIFIC	GRAVITY	OF PRODUCT					`\						•				
	PRODUCT	THICKNESS					,10.			·							
	DEPTH TO	WATER	77:01	10.58	9.83	51.01	10.03	r									
	DEPTH TO	PRODUCT					10.02						-				
	TOP OF CASING	ELEVATION	,6966	,00.00	99.31	99.49	44. #8.										
	WELL	DEPTH		:		15	9/										, .
	WELL	<u>0</u>	-	2	3	=	70										COMMENTS: